(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 23 January 2003 (23.01.2003)

PCT

(10) International Publication Number WO 03/007623 A3

(51) International Patent Classification⁷: H04Q 1/00, G05B 19/00

(21) International Application Number: PCT/US02/21903

(22) International Filing Date: 10 July 2002 (10.07.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 60/304,216 10 July 2001 (10.07.2001)

(71) Applicant: AMERICAN EXPRESS TRAVEL RE-LATED SERVICES COMPAGNY, INC [US/US]; American Express Tower, World Financial Center, New York, NY 10285-4900 (US).


(72) Inventors: BERARDI, Michael, J.; 7770 NW 50th Street, #306, Lauderhill, FL 33313 (US). BLIMAN, Michal; 4 Dogwood Circle, Matawan, NJ 07747 (US). BONALLE, David, S.; 77 Rose Hill Avenue, New Rochelle, NY 10804 (US). ELWOOD, Jennifer, Anne; 115 East 34th Street, Apt. #8-G, New York City, NY 10016 (US). HOOD, Matthew, C.; 1112 LaFayette Road, Wayne, PA 19087 (US). ISENBERG, Susan, E.; 201 West 74 th, 12 th, New York City, NY 10012 (US). MAYERS, Alexandra; 49 Grove Street, #5-B, New York City, NY 10014 (US). SAUNDERS, Peter, D.; 3710 East Palisade Drive, Salt Lake City, UT 84109 (US). SCHEDING, Kathryn, D.; 12301 Clover Avenue, Los Angeles, CA 90066 (US). SHAH, Sejal, Ajit; 230 East 30th Street, #11-J, New York City, NY 10016 (US). WILLIAMSON, John, R.; 302 Pavonia Avenue, Jersey City, NJ 07302 (US).

- (74) Agent: SOBELMAN, Howard, I.; Snell & Wilmer L.L.P., One Arizona Center, 400 East Van Buren, Phoenix, AZ 85004-2202 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR PAYMENT USING RADIO FREQUENCY IDENTIFICATION IN CONTACT AND CONTACTLESS TRANSACTIONS

US



(57) Abstract: A transporter-reader payment system includes a fob (102) including a transponder (114), and a RFID reader (104) for interrogating the transponder (102). The system may further include a personalization system (134) for populating onto the fob (102) and RFID reader (104) identifying information and security and authentification keys which may be used during mutual authentication of the fob (102) and the reader (104) and for completing a transaction. In exemplary operation, the fob (102) and RFID reader (104) may be personalized, the fob (102) may be presented to the RFID reader (104) for interrogation, the fob (102) and reader (104) may engage in mutual authentication, and fob (102) identifying information may be provided to the reader (104) for transaction completion. In another exemplary embodiment, operation of the transponder-reader payment system may be controlled by an activation circuit. Further, the fob (102) may be responsive to multiple interrogation signals.





SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

(88) Date of publication of the international search report: 10 April 2003

Date of publication of the amended claims: 31 July 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

[Received by the International Bureau on February 28, 2003 (28.02.03): original claims 1-62 replaced by amended claims 1-59 (pages 29-40)]

- 1. A transponder-reader payment system comprising:
- a. a Radio Frequency Identification (RFID) reader operable to provide a radio frequency (RF) interrogation signal for powering a transponder system, receiving a transponder system RF signal, and communicating a transponder system account data related to said transponder system RF signal to a merchant system, said RFID reader including,
 - i. a first interrogator for providing a first RF interrogation signal;
 - ii. a RFID authentication circuit in communication with said interrogator;
- iii. a RFID database, in communication with said RFID authentication circuit, said database operable to store at least one of a RFID reader identifying data, a transponder system decryption security key, a RFID reader and encryption security key and a transponder authentication key;
- iv. at least one of a serial interface and a universal serial bus (USB) interface; and
- v. a RFID protocol/sequence controller in communication with at least one of said first interrogator, said RFID authentication circuit, said RFID database, and said USB interface, said RFID protocol/sequence controller configured to facilitate control of the order of operation of said interrogator, said RFID authentication circuit, said RFID database, and said USB interface.
- 2. A system according to claim 1 further comprising:
- a. a transponder system operable to receive said first RF interrogation signal, authenticate said first RF interrogation signal, and transmit said transponder system account data, said transponder system comprising:
 - i. a first transponder responsive to said RF interrogation signal;

40

ii. a first transponder system antenna configured to receive said first RF interrogation signal;

- iii. a second transponder responsive to a second RF interrogation signal, said first RF interrogation signal different from said second RF interrogation signal;
- iv. a second transponder system antenna configured to receive said second RF interrogation system;
- v. a transponder system authentication circuit in communication with at least one of said first transponder and said second transponder; and
- vi. a transponder system database in communication with said transponder system authentication circuit.
- 3. A system according to claim 2, wherein said transponder system further includes:
 - a. a transponder system USB interface; and
- b. a transponder system protocol/sequence controller in communication with at least one of said first transponder, said second transponder, said transponder system USB interface, said transponder system authentication circuit, and said transponder system database, said transponder system protocol/sequence controller configured to control the order of operation of said first transponder, said second transponder, said transponder system authentication circuit, said transponder system database, and said transponder system USB interface.
- 4. A system according to claim 1, wherein said RFID reader further includes:
- a. a second interrogator, said second interrogator operable to send a second RF interrogation signal; and
- b. a RFID communications interface configured to communicate with a merchant system, said communications interface operable to provide said transponder system account data.

5. A system according to claim 4, wherein said RFID reader further includes a first antenna in communication with said first interrogator and a second antenna in communication with said second interrogator, wherein said first antenna is operable to provide said first RF interrogation signal to said first transponder and said second interrogator is operable to provide said second RF interrogation signal to said second transponder.

- 6. A system according to claim 1, wherein said RFID database is operable to store a transponder system personal identification number (PIN).
- 7. A system according to claim 5, wherein said RFID reader further comprises at least one of a RFID internal antenna, and a RFID external antenna, said RFID internal antenna and said RFID external antenna configured to provide at least one of said first RF interrogation signal and said second RF interrogation signal.
- 8. A system according to claim 3, wherein said transponder system protocol/sequence controller is responsive to at least one of said first RF interrogation signal and said second RF interrogation signal, said transponder protocol/sequence controller controlling the sequence of operation at least one of said transponder system authentication circuit, said transponder system database, and said transponder system USB interface in response to at least one of said first RF interrogation signal and said second RF interrogation signal.
- 9. A system according to claim 3, wherein said transponder system protocol/sequence controller is configured to activate said transponder system authentication circuit in response to said first RF interrogation signal, said transponder system authenticating circuit configured to provide an encrypted RF interrogation signal, said transponder system authentication circuit configured to provide said encrypted RF interrogation signal to said first transponder for providing to said RFID reader.
- 10. A system according to claim 9, wherein said RFID reader is configured to receive said encrypted RF interrogation signal, said transponder system protocol/sequence controller

activating said transponder system authentication circuit in response to said encrypted RF interrogation signal.

- 11. A system according to claim 10, wherein said RFID database is configured to provide a transponder system decryption key to said RFID authentication circuit in response to said encrypted RF interrogation signal, said transponder system decryption key for use in decrypting said encrypted RF interrogation signal, providing a decrypted RF interrogation signal, said transponder system decryption key provided to said RFID reader based on an unique transponder identification code.
- 12. A system according to claim 11, wherein said RFID authentication circuit is configured to compare said decrypted RF interrogation signal and said RF interrogation signal to determine whether a match exists.
- 13. A system according to claim 12, wherein said RFID protocol/sequence controller is configured to activate at least one of said USB interface and said RFID communication interface where said RFID authentication circuit matches said decrypted RF interrogation signal and said RF interrogation signal.
- 14. A system according to claim 13, wherein said transponder system protocol/sequence controller activates said transponder system authentication circuit in response to at least one of said first RF interrogation signal and said second RF interrogation signal.
- 15. A claim according to claim 14, wherein said transponder system authentication circuit is configured to provide a transponder authentication code to at least one of said first transponder and said second transponder for providing to said RFID reader.
- 16. A system according to claim 15, wherein said RFID reader is configured to receive said transponder authentication code, said RFID protocol/sequence controller activating said RFID authentication circuit in response to said transponder authentication code, said RFID authentication circuit configure to encrypt said transponder authentication code.

17. A system according to claim 16, wherein said RFID reader is configured to provide said encrypted authentication code to said transponder system.

- 18. A system according to claim 17, wherein said transponder system database is operable to store at least one of a transponder system identification data, a RFID reader decryption security key, and a transponder system account data.
- 19. A system according to claim 18, wherein said transponder system database is configured to provide said RFID reader decryption security key to said transponder system authentication circuit in response to said encrypted authentication code, said RFID reader decryption key for use in decrypting said encrypted transponder authentication code and providing a decrypted transponder authentication code.
- 20. A system according to claim 19, wherein said transponder system authentication circuit is configured to compare said decrypted transponder authentication code and said transponder authentication code to determine if a match exists.
- 21. A system according to claim 20, wherein said account data is in magnetic stripe format.
- 22. A system according to claim 21, wherein said transponder system transaction account data is pre-encrypted.
- 23. A system according to claim 22, wherein said transponder system database is configured to provide said pre-encrypted transponder system account data to said RFID reader where said transponder system authentication circuit matches said decrypted transponder authentication code and said transponder authentication code.
- 24. A system according to claim 23, wherein said RFID communications interface is configured to provide said transponder system PIN and said pre-encrypted transponder system account data where said transponder authentication code matches said decrypted

transponder authentication code, and said decrypted RF interrogation signal matches said RF interrogation signal.

- 25. A system according to claim 24, wherein said transponder system further comprises a switch, said switch operable to enable or disable operation of said transponder system.
- 26. A system according to claim 25, wherein said switch is configured to place the transponder system in at least one of a selectivity mode and an inclusivity mode.
- 27. A system according to claim 25, wherein said switch is mechanical.
- 28. A system according to claim 25, wherein said switch is configured to respond to a logic circuit.
- 29. A system according to claim 2, wherein said transponder system further includes an internal power source.
- 30. A system according to claim 29, wherein said switch is in communication with said internal power source, said switch responsive to said internal power source.
- 31. A system according to claim 29, wherein said transponder system further includes a biometric circuit, said biometric circuit in communication with said internal power source.
- 32. A system according to claim 25, wherein said switch is a biometric circuit, said biometric circuit operable to enable or disenable operation of said transponder system.
- 33. A system according to claim 32, wherein said biometric circuit is configured to place said transponder system in one of a selectivity mode and an inclusivity mode.
- 34. A system according to claim 7, wherein said RFID reader includes a RFID PIN keypad, said RFID PIN keypad configured to receive said transponder PIN, said RFID reader configured to compare said transponder PIN to said received transponder PIN, said RFID reader operable to provide at least one of said received transponder PIN, said transponder PIN, or a verification of said received transponder PIN, verification of received transponder

45

PIN provided where said RFID reader matches said transponder PIN to said received transponder PIN.

- 35. A system according to claim 7, wherein said RFID reader is configured to provide said transponder PIN to a payment authorization center for verification of said transponder PIN.
- 36. A system according to claim 34, wherein said merchant system includes a merchant system PIN keypad, said merchant system PIN keypad configured to receive said transponder PIN from said merchant system PIN keypad, said merchant system configured to provide said transponder PIN to said payment authorization center for verification.
- 37. A system according to claim 31, wherein said biometric circuit is configured to provide a biometric data verification response, said biometric circuit configured to provide said biometric data verification response to at least one of said RFID reader and said merchant system, wherein said biometric data verification response is an identification verification data.
- 38. A system according to claim 3, further comprising a personalization system operable to initialize at least one of said transponder system and said RFID reader to transponder-reader payment system parameters.
- 39. A system according to claim 38, wherein said personalization system is in communication with said transponder system using at least one of a USB connector and RF communications.
- 40. A system according to claim 39, wherein said personalization system is in electrical communications with said RFID reader.
- 41. A system according to claim 40, wherein said personalization system is operable to populate at least one of said RFID reader identifying data, transponder system decryption security key, RFID encryption security key, and transponder PIN on said RFID database.

42. A system according to claim 41, wherein said personalization system is operable to populate at least one of said transponder system identification data, a RFID reader decryption security key, a transponder encryption authentication security key, a transponder system transactional account data, and a transponder system authentication security key onto said transponder system database.

- 43. A system according to claim 2, wherein said RFID reader is operable to initialize said transponder.
- 44. A system according to claim 2, wherein said RFID reader is in RF communication with said transponder system, said RFID reader operable to populate at least one of said transponder system identification data, a RFID reader decryption security key, a transponder system transactional account data onto said transponder system database.
- 45. A transponder-reader payment system including a transponder system operable to receive a first RF interrogation signal, and authenticate said first RF interrogation signal, said transponder system comprising:
 - a. a first transponder responsive to said first RF interrogation signal;
- b. a second transponder responsive to a second RF interrogation signal, said first RF interrogation signal different from said second RF interrogation signal;
- c. a first transponder system antenna configured to receive said first RF interrogation signal; and
- d. a second transponder system antenna configured to receive said second RF interrogation signal.
- 46. A system according to claim 45, wherein said transponder system further includes at least one of a transponder system USB interface, transponder system authentication circuit, and a transponder system serial interface.
- 47. A transponder-reader payment system comprising:

a. a RFID reader operable to provide a RF interrogation signal for powering a transponder system, receiving a transponder system RF signal, and communicating a transponder system account data related to said transponder system RF signal to a merchant system, said RFID reader including:

- i. a first RFID reader antenna in communication with a first interrogator for providing a first RF interrogation signal; and
- ii. a second RFID reader antenna in communication with a second interrogator, for providing a second RF interrogation signal;
- b. a transponder system operable to receive at least one of said first and second RF interrogation signal, authenticate said received interrogation signal, and transmit a transponder system account data, said transponder system comprising:
- i. a first transponder antenna in communication with a first transponder, said first transponder responsive to said first RF interrogation signal; and
- ii. a second transponder antenna in communication with a second transponder, said second transponder responsive to said second RF interrogation signal.
- 48. A system according to claim 47, wherein said RFID reader includes at least one of a a RFID reader authentication circuit, a RFID reader serial interface and a RFID reader USB interface, and said transponder system includes at least one of a transponder system USB interface, transponder system authentication circuit, and a transponder system serial interface.
- 49. A method of transponder-reader payment comprising the steps of:
- a. providing a transponder system, the transponder system responsive to a plurality of interrogation signals, the transponder system storing at least one of an account data, an account name, and account expiration date, the transponder system including at least a first transponder responsive to a first interrogation signal and a second transponder responsive to a second interrogation signal; and

b. providing a RFID reader, said reader configured to provide at least one of the interrogation signals.

- 50. A method according to claim 49, further comprising the steps of:
 - a. encrypting the transponder system account data;
 - b. initializing the transponder system;
 - c. initializing the RFID reader;
 - d. mutually authenticating the RFID reader and the transponder system;
- e. providing the encrypted account data from the transponder system to the RFID reader;
 - f. decrypting the encrypted account data; and
 - g. providing the decrypted account data to a merchant system.
- 51. A method according to claim 50, wherein mutual authenticating includes the RFID reader authenticating the transponder system, and the transponder system authenticating the RFID reader.
- 52. A method according to claim 51, wherein mutual authentication includes:
- a. providing an interrogation signal from the RFID reader to the transponder system;
- b. encrypting the interrogation signal at the transponder system to form an encrypted authentication interrogation signal;
 - c. providing the encrypted authentication interrogation signal to the RFID reader;
- d. decrypting the encrypted authentication interrogation signal at the RFID reader, decrypting including using a transponder system decryption security key;
 - e. matching the interrogation signal to the decrypted interrogation signal;

f. providing an authorization code from the transponder system to the RFID reader;

- g. encrypting the authorization code at the RFID reader to form an encrypted authorization code;
 - h. providing the encrypted authorization code to the transponder system;
- i. decrypting the encrypted authorization code at the transponder system,
 decrypting including using a RFID reader decryption security key; and
 - j. matching the authorization code to the decrypted authorization code.
- 53. A method according to 52, where initializing the transponder system includes populating at least one of a transponder system identification data, a RFID reader decryption security key, a transponder system transactional data, and an encrypted transponder PIN onto a transponder system database.
- 54. A method according to claim 53, wherein initializing the RFID reader includes populating at lease one of a transponder system identification data, a RFID reader decryption security key, a transponder system transactional data, and an encrypted transponder PIN onto a transponder system database.
- A method according to claim 49, wherein initializing the RFID reader includes populating at least one of a RFID reader identifying data, a transponder system decryption security key, a RFID encryption security key, and a transponder PIN onto a RFID database using a USB interface.
- A method according to claim 53, wherein initializing the transponder system includes populating at least one of a transponder system identifying data, a RFID reader decryption security key, and a transponder system transaction data using a USB interface.
- 57. A method according to claim 49, wherein initialing the transponder system, includes initializing said transponder system using a RFID reader.

58. A method according to claim 54, including using a switch to enable the transponder system, the switch consisting of at least one of a mechanical switch, a logic switch, and a biometric switch.

59. A method according to claim 58, including providing a secondary identification in response to a request from a merchant system.

PATENT COOPERATION TREATY

From the INTERNATIONAL SEARCHING AUTHORITY

To: HOWARD I. SOBELMAN SNELL & WILMER L.L.P	PCT				
ONE ARIZONA CENTER 400 EAST VAN BUREN PHOENIX, AZ 58004-2202	NOTIFICATION OF TRANSMITTAL OF THE INTERNATIONAL SEARCH REPORT OR THE DECLARATION				
	(PCT Rule 44.1)				
	Date of Mailing (day/month/year) 30 UEC 2002				
Applicant's or agent's file reference 40655.7016	FOR FURTHER ACTION See paragraphs 1 and 4 below				
International application No. PCT/US02/21903	International filing date (day/month/year)				
Applicant AMERICAN EXPRESS TRAVEL RELATED SERVICES CO	10 July 2002 (10.07.2002) . , INC				
The applicant is hereby notified that the international search report has been established and is transmitted herewith.					
Filing of amendments and statement under Article 19: The applicant is entitled, if he so wishes, to amend the claims of the international application (see Rule 46):					
When? The time limit for filing such amendments is normally two months from the date of transmittal of the international search report.					
Where? Directly to the International Bureau of WIPO, 34, chemin des Colombettes 1211 Geneva 20, Switzerland, Facsimile No.: (41-22) 740.14.35					
For more detailed instructions, see the notes on the accompanying sheet.					
2. The applicant is hereby notified that no international search report will be established and that the declaration under Article 17(2)(a) to that effect is transmitted herewith.					
3. With regard to the protest against payment of (an) addi	tional fee(s) under Rule 40.2, the applicant is notified that:				
the protest together with the decision thereon has been transmitted to the International Bureau together with the applicant's request to forward the texts of both the protest and the decision thereon to the designated Offices.					
no decision has been made yet on the protest; the a	pplicant will be notified as soon as a decision is made.				
4. Reminders					
Shortly after 18 months from the priority date, the international application will be published by the International Bureau. If the applicant wishes to avoid or postpone publication, a notice of withdrawal of the international application, or of the priority claim, must reach the International Bureau as provided in Rules 90 bis.1 and 90 bis.3, respectively, before the completion of the technical preparations for international publication.					
examination must be filed if the applicant wishes to postpone to	et of some designated Offices, a demand for international preliminary the entry into the national phase until 30 months from the priority date thin 20 months from the priority date, perform the prescribed acts for				
In respect of other designated Offices, the time limit of 30 months (or later) will apply even if no demand is filed within 19 months.					
See the Annex to Form PCT/IB/301 and, for details about the a Volume II, National Chapters and the WIPO Internet site.	applicable time limits, Office by Office, see the PCT Applicant's Guide,				
Name and mailing address of the ISA/US Commissioner for Patents	Authorized officer				
Box PCT Washington, D.C. 20231	Brian A Zimmerman				
Facsimile No. (703)305-3230 Form PCT/ISA/220 (April 2002)	Telephone No. 703-3QS-47DO (See notes on accompanying sheet)				

RECEIVED

JAN 0 6 2003

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's 40655.7016	or agent's file reference	FOR FURTHER ACTION		cation of Transmittal of International Search Report T/ISA/220) as well as, where applicable, item 5				
International PCT/US02/	l application No. 21903	International filing date (day/mor 10 July 2002 (10.07.2002)		(Earliest) Priority Date (day/month/year) 10 July 2001 (10.07.2001)				
Applicant AMERICAN EXPRESS TRAVEL RELATED SERVICES CO., INC								
This international search report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau. This international search report consists of a total of								
	It is also accompanie	d by a copy of each prior art doc	iment cite	d in this report.				
Basis of the Report a. With regard to the language, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.								
the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)). b. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international search was carried out on the basis of the sequence listing:								
	contained in the internation	al application in written form.						
	filed together with the inter	national application in computer re	adable for	m.				
	furnished subsequently to the	his Authority in written form.						
	furnished subsequently to the	his Authority in computer readable	form.	_				
	the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.							
	the statement that the information been furnished.	mation recorded in computer reada	ble form is	identical to the written sequence listing has				
2.	Certain claims were found	l unsearchable (See Box I).						
3 4. With								
	the text is approved as submitted by the applicant.							
	the text has been establishe	d by this Authority to read as follo	ws:					
5. With	5. With regard to the abstract,							
	the text is approved as subr	mitted by the applicant.						
	the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.							
6. The fi	6. The figure of the drawings to be published with the abstract is Figure No. 1A							
	as suggested by the applica	nt.		None of the figures				
	because the applicant failed	l to suggest a figure.						
	because this figure better cl	haracterizes the invention.						

Form PCT/ISA/210 (first sheet) (July 1998)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/21903

Box III TEXT OF THE ABSTRACT (Continuation of Item 5 of the first sheet)

The technical features mentioned in the abstract do not include a reference sign between parentheses (PCT Rule 8.1(d)).

NEW ABSTRACT

A transponder-reader payment system includes a fob (102) including a transponder (114), and a RFID reader (104) for interrogating the transponder (102). The system may further include a personalization system (134) for populating onto the fob (102) and RFID reader (104) identifying information and security and authentication keys which may be used during mutual authentication of the fob (102) and the reader (104) and for completing a transaction. In exemplary operation, the fob (102) and RFID reader (102) may be personalized, the fob (102) may be presented to the RFID reader (104) for interrogation, the fob (102) and reader (104) may engage in mutual authentication, and fob (102) identifying information may be provided to the reader (104) for transaction completion. In another exemplary embodiment, operation of the transponder-reader payment system may be controlled by an activation circuit. Further, the fob (102) may be responsive to multiple interrogation signals.

Form PCT/ISA/210 (continuation of first sheet(2)) (July 1998)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/21903

	TOYER OF THE STORY AND THE STO					
A. CLASSIFICATION OF SUBJECT MATTER						
IPC(7) : H04Q 1/00; G05B 19/00						
	US CL : 705/17, 18; 340/5.52,5.6, 5.82					
According to International Patent Classification (IPC) or to both national classification and IPC						
B. FIEL	DS SEARCHED					
Minimum do	cumentation searched (classification system followed	by classification symbols)				
	05/17, 18; 340/5.52,5.6, 5.82	· · · · · · · · · · · · · · · · · · ·				
	, , , , , , , , , , , , , , , , , , , ,					
Documentati	on searched other than minimum documentation to the	e extent that such documents are included	i in the fields searched			
			1			
Electronic da	ata base consulted during the international search (nar	ne of data base and, where practicable, s	earch terms used)			
		•	•			
	•					
	UMENTS CONSIDERED TO BE RELEVANT					
Category *	Citation of document, with indication, where a	propriate, of the relevant passages	Relevant to claim No.			
X	US 6,073,840 A (MARION) 13 June 2000, Abstrac	t and description of figures 4a,4b,5	1,6,7,36-38,50,52-62			
	and 6	-				
Y			2-5,8-35,39-49			
x	US 5,519,381 A (MARSH) 21 May 1996, column 3	50				
•		********				
Y			2-5,8-35,39-49			
	,					
······						
Burtha	r documents are listed in the continuation of Box C.	San autom familia anna				
		See patent family annex.				
• s	pecial categories of cited documents:	"T" later document published after the inte date and not in conflict with the applic				
"A" document	defining the general state of the art which is not considered to be	principle or theory underlying the inve				
of partica	ilar relevance					
"E" carlier an	oplication or patent published on or after the international filing date	"X" document of particular relevance; the considered novel or cannot be considered.				
_	•	when the document is taken alone	ion to mitero an intentite step			
	t which may throw doubts on priority claim(s) or which is cited to		atatu at turnatur i			
establish specified	the publication date of another citation or other special reason (as	"Y" document of particular relevance; the considered to involve an inventive ster				
		combined with one or more other such				
"O" document	t referring to an oral disclosure, use, exhibition or other means	being obvious to a person skilled in the	e art			
P document	t published prior to the international filing date but later than the	"&" document member of the same patent	family			
priority date claimed						
Date of the actual completion of the international search Date of the international search report						
Date of the actual completion of the international search Date of the international search report						
	.002 (04.10.2002)	2 2 2 2 2 1				
	ailing address of the ISA/US	Authorized officer	1711			
	nmissioner of Patents and Trademarks	Brian A Zimmerman M MMM A MMM				
Box PCT Washington, D.C. 20231		ן לעשעון ועישושון וו				
Facsimile No. (703)305-3230 Telephone No. 703-305-4700						

Form PCT/ISA.'210 (second sheet) (July 1998)